

HYSPEC FORKLIFTS

HDW Series

Diesel 5 - 10 Tonnes



High specification at Competitive prices
materials handling solution

High Specification

HYSPEC FORKLIFT TRUCKS are built to a high standard using quality international components, with a range of machines 1 to 10 tonnes in LPG/DIESEL or ELECTRIC.

High Quality Components

Quality components mean less down time keeping the truck running longer.

Technical Support

Technical support is available to the dealer and user from people who know the Material Handling business, and are dedicated to make Hyspec Forklifts second to none.

Serviceability

Hyspec forklift trucks are easy to service and maintain, one piece bonnets are used on all the range, giving easy access to carry out service or daily checks.

HYSPEC FORKLIFTS

Unit 1, Orchardside, Hards Lane,
Frognall, Peterborough PE6 8RP
Tel: 01778 344737 Fax: 01778 348147
E-mail: sales@hyspeceuro.com
www.hyspeceuro.com

HYSPEC FORKLIFTS HDW Series Diesel 5 - 10 Tonnes

SPECIFICATIONS

		HD50W	HD60W	HD70W	HD80W	HD100W		
General	1 Model							
	2 Power type	diesel						
	3 Load capacity	kg	5000	6000	7000	8000	10000	
	4 Load centre	mm	600					
Dimensions	5 Lift height	mm	3000					
	6 Free lift height	mm	195		200			
	7 Fork size	L x W x T	mm	1220x150x60	1220x150x65	1500x160x75	1500x160x80	
	8 Fork spread outside	Min./Max.	300/1700		320/2015	420/2144		
	9 Mast tilt angle	FWD/BWD	deg 6°/12°					
	10 Front overhang	mm	622		700	733		
	11 Length to face of fork	mm	3472	3592		3940	4258	
	12 Overall width	mm	1995		2245	2245		
	13 Mast lowered height	mm	2500		2695	2845		
	14 Mast extended height	mm	4419		4374	4297		
	15 Overhead guard height	mm	2420		2565	2565		
	16 Turning radius	mm	3300	3450		3700	3900	
	17 Right angle aisle width	mm	3000	3090		3310	3540	
Performance	18 Travel speed (no load/full load)	km/h	28/26		28/24	28/24		
	19 Lift speed (no load/full load)	mm/sec	500/370	500/330	500/320	410/350	350/300	
	20 Max. gradeability	%	20					
	21 Weight	kg	8340	8840	9350	11080	12860	
Chassis	22 Tyres	Front	8.25-15-14PR		9.00-20-14PR			
		Rear	8.25-15-14PR		9.00-20-14PR			
	24 Tread	Front	mm	1470		1600		
		Rear	mm	1700		1700		
	26 Wheelbase	mm	2250		2500	2800		
	27 Ground clearance (no load/full load)	Mast	mm	160		245/205		
		Frame	mm	N/A		343/323		
	Drive unit & control	29 Battery	V/AH	2X12/100				
30 Engine		Model	6BG1QC-02					
		Manufacturer	ISUZU					
		Rated power	kw/rpm	82.3/2000		82.4/2000		
		Rated torque	Nm/rpm	416/1400-160		415/1400-160		
		No. of Cylinder		6				
		Bore x stroke	mm	105X125				
		Displacement	L	6.494				
37 Fuel tank capacity		L	140					
38 Transmissions		Shift (front/rear)	2/2					
39 Operating pressure		MPa	17	17	17	17	18	

